



BACK BAR DISPLAY REFRIGERATED CABINETS

**COLDTEK
MODEL NO. SC-128F**



**COLDTEK
MODEL NO. SC-208F**



**COLDTEK
MODEL NO. SC-318F**



**COLDTEK
MODEL NO. SC-128FS**






**COLDTEK
MODEL NO. SC-208FS**






**COLDTEK
MODEL NO. SC-318FS**



COLDTEK**BACK BAR DISPLAY REFRIGERATED CABINETS****SPECIFICATIONS – FOR STANDARD FINISH**

ITEM	DESCRIPTION		
PICTURE			
COOLING SYSTEM	FAN COOLING SYSTEM		
NET VOLUME	128 LITRES	208 LITRES	318 LITRES
INTERNAL DIMENSION	410*355*745 (mm)	810*355*745 (mm)	1245*355*745 (mm)
EXTERNAL DIMENSION	600*500*840 (mm)	900*500*840 (mm)	1335*500*840 (mm)
PACKING DIMENSION	650*560*900 (mm)	955*560*900 (mm)	1390*560*900 (mm)
COOLING PERFORMANCE	2-10°C		
NET WEIGHT	35 kg	66 kg	75 kg
GROSS WEIGHT	37 kg	68 kg	78 kg
INSULATION MATERIAL	CYCLOPENTANE		
NO. OF SHELF	2	4	6
DOOR INSULATION	DOUBLE GLAZED WITH ARGON GAS INSIDE		
DOOR TYPE	HINGED & LOCKABLE		
DOOR FRAME	BLACK PLASTIC		
LIGHTING	INTERNAL LED LIGHT		
INPUT POWER	135 watts	175 watts	190 watts
REFRIGERANT	R600a		
VOLTAGE SUPPLY	110V-120V/60HZ, 220-240V/50HZ		
BODY COLOR	BLACK		
INNER BODY	EMBOSSSED ALUMINIUM PLATE		
OUTER BODY	POWDER COATED STEEL PLATE		
CERTIFICATE	CE / CB	ISO9001 / CE / ROHS / SAA	CE / ROHS / SAA

SPECIFICATIONS – FOR STAINLESS STEEL FINISH

ITEM	DESCRIPTION		
PICTURE			
COOLING SYSTEM	FAN COOLING SYSTEM		
NET VOLUME	128 LITRES	208 LITRES	318 LITRES
INTERNAL DIMENSION	410*355*745 (mm)	810*355*745 (mm)	1245*355*745 (mm)
EXTERNAL DIMENSION	600*500*840 (mm)	900*500*840 (mm)	1335*500*840 (mm)
PACKING DIMENSION	650*560*900 (mm)	955*560*900 (mm)	1390*560*900 (mm)
COOLING PERFORMANCE	2-10°C	2-10°C	2-10°C
NET WEIGHT	35 kg	66 kg	75 kg
GROSS WEIGHT	37 kg	68 kg	78 kg
INSULATION MATERIAL	CYCLOPENTANE		
NO. OF SHELF	2	4	6
DOOR INSULATION	DOUBLE GLAZED WITH ARGON GAS INSIDE		
DOOR TYPE	HINGED & LOCKABLE		
DOOR FRAME	304 STAINLESS STEEL		
LIGHTING	1 HORIZONTAL LED LIGHT		
INPUT POWER	135 watts	175 watts	190 watts
REFRIGERANT	R600a		
VOLTAGE SUPPLY	110V-120V/60HZ, 220-240V/50HZ		
INNER BODY	MIRROR FINISHED STAINLESS STEEL		
OUTER BODY	304 STAINLESS STEEL (as per requirement)		
CERTIFICATE	CE / CB	ISO9001 / CE / ROHS / SAA	CE / ROHS / SAA

