## Flexdrawer Counter



## **Features**

- ◆ CFC free refrigerant and foam
- ◆ AISI 304 stainless steel framework construction
- ◆ User friendly controls with LED temperature display
- ◆ Change drawer temperature from fridge to freezer at the touch of a button
- ♦ HC refrigerant




G-CBR1-2





G-CBR2-2






G-CBR2-2







Model	Ext. Dimension W×D×H (mm)	Int Dimension W×D×H (mm)	Capacity (L)	Temperature (°C)	GN1/1 PANS	Power Supply
G-CBR1-2	905×700×565	675×565×205	78	+1 ~ +4°C/-18 ~ -21°C	2 pcs	230V/50Hz
G-CBR2-2	905×700×830	675×565×470	179	+1 ~ +4°C/-18 ~ -21°C	4 pcs	230V/50Hz


- ◆ Automatic energy saving hot gas defrost
- ◆ Magnetic gaskets can be replaced without any tools
- ◆ GN1/1 150mm deep pan capacity maximises available storage space
- ◆ Climate Class 5(43°C ambient)








G-CBR1-3

G-CBR2-3









Model	Ext. Dimension W×D×H (mm)	Int Dimension W×D×H (mm)	Capacity (L)	Temperature (°C)	GN1/1 PANS	Power Supply
G-CBR1-3	1230×700×565	1000×565×205	116	+1 ~ +4°C/-18 ~ -21°C	3 pcs	230V/50Hz
G-CBR2-3	1230×700×830	1000×565×470	265	+1 ~ +4°C/-18 ~ -21°C	6 pcs	230V/50Hz





